

MEMCOR®

SPECIFICATION SHEET

MEMCOR® Modules



MEMCOR® Pressurised and Submerged membrane modules are used for a wide range of applications. The details and application information for each module type are shown in the following pages.

Performance values presented in the attached pages are typical only and do not represent a performance guarantee. Performance guarantees for any project only apply when confirmed in writing by Memcor Australia Pty Ltd with specific reference to the project in question



SPECIFICATION SHEET

MEMCOR® Modules

MEMCOR® Pressurised Membranes

Module Parameters

Module Model	L10V	L10U	L20V
Membrane Material	PVDF	PVDF	PVDF
Backwash Type	Air Scour Liquid B/W	Air Scour Liquid B/W	Air Scour Liquid B/W
Nominal Pore Size (µm)	0.04	0.04	0.04
Surface Area (m ²)	23.4	18.7	38.1
Maximum Temp (°C)	45	45	45
pH Range	2-10	2 -10	2 -10
Average Free Chlorine (ppm)	< 5	< 5	< 5
Maximum Free Chlorine (ppm)	1000	1000	1000
Module Weight Wet (kg)	6.5	6.0	9.0
Nominal Module Length (mm)	1157	1157	1800
Nominal Module Diameter (mm)	119	119	119
Typical Applications	General Applications	High Solids & General Applications	General Applications





SPECIFICATION SHEET

MEMCOR[®] Modules

Module Performance

Module Model	L10V	L10U	L20V
Membrane Material	PVDF	PVDF	PVDF
Chlorinated Secondary Effluent			
Module Flow (kL/day)	30.3		49.4
Recovery	93%		94%
Clear Surface Water			
Module Flow (kL/day)	38.5		62.7
Recovery	95%		96%
Turbid Surface Water			
Module Flow (kL/day)	30.3	24.2	49.4
Recovery	94%	93%	94%
Surface Water - with Algae or coagulant			
Module Flow (kL/day)		26.3	
Recovery		93%	
Sea Water			
Module Flow (kL/day)	35.7		58.3
Recovery	95%		95%
Chlorinated Municipal Water			
Module Flow (kL/day)	55.0		89.5
Recovery	> 96%		> 96%



SPECIFICATION SHEET

MEMCOR® Modules

Feed Water

The specifications above give indicative performance for a range of water sources. The characteristics of these water sources are tabulated below:

Water Type	Turbidity	SS	BOD	TOC	Ammonia	Coag.	Total Chlorine	Free Chlorine
	NTU	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L
Chlorinated Secondary Effluent	< 10	< 50	20	N/A	> 3	Nil	1 - 3	Nil
Clear Surface Water	< 10	1	N/A	< 2	N/A	Nil	Nil	Nil
Turbid Surface Water	10 - 100	< 100	N/A	< 10	N/A	< 5	Nil	Nil
Surface Water with Algae or Coagulant	100 - 200	< 100	N/A	< 15	N/A	5 - 20	Nil	Nil
Sea Water	10 - 40	10 - 30	N/A	< 2	N/A	Nil	< 2	< 2
Chlorinated Municipal Water	< 1	0.1	N/A	< 1	N/A	Nil	< 2	< 2

Contact Memcor Australia for advice on treatment of feed waters that are outside the range of qualities given above, or where performance guarantees are required.